



ENAMELED BUFFER TANKS					
TECHNICAL DATA					
Model	...	BCE 150K60	BCE 200K60	BCE 300K	BCE 500K80
Volume group	...	150	200	300	500
Energy efficiency class	...	B	B	B	B
Standing loss heat	W	45	53	50	73
Rated pressure	MPa	0.6	0.6	0.6	0.6
Volume	L	147	193	272	491
Insulation thickness	mm	75	75	85	80
Gross weight	kg	53	60	72	124
CONNECTIONS					
1: Inlet / Outlet		G1 1/2 F	G1 1/2 F	G1 1/2 F	G2 F
2: Flange		Yes	Yes	Yes	Yes
3: Socket for thermostat		G1/2 F	G1/2 F	G1/2 F	G1/2 F
4: Additional socket		G1 1/2 F	G1 1/2 F	G1 1/2 F	G1 1/2 F
5: Recirculation		G1 1/2 F	G1 1/2 F	G1 1/2 F	G2 F
6: Inlet / Outlet		G3/4 F	G3/4 F	G3/4 F	G1 1/4 F
DIMENSIONS					
A	mm	195	195	200	225
C	mm	615	780	890	970
D	mm	600	600	670	800
G	mm	75	75	85	80
H	mm	1150	1430	1605	1765
L	mm	900	1170	1330	1470
M	mm	690	690	760	890